



# SNOW FILLER

LIGHT WEIGHT SPARKLING COMPOUND

## TECHNICAL DATA SHEET

REV: 04

Date: 30 April 2024

### DESCRIPTION

**Snow Filler Light Weight Sparkling Compound** is a ready-mixed lightweight filler provides a dry time color indicator that will turn from pink colour when it is wet to white colour when it is dry. It is specially formulated for repairs walls and ceilings. It is easy to apply, dries fast and will not crack, shrink or sag..

### FEATURES

- ◆ Only one application needed.
- ◆ One part no mixing.
- ◆ Environmental friendly, easily clean up with water.
- ◆ Minimal shrinkage and cracking.
- ◆ Fast drying and can be sanded and painted after set.
- ◆ Smart indication – pink colour when it is wet and white colour when it is dry.
- ◆ The white colour after dried is irreversible with water after 24 hours depending on temperature, relative humidity and depth of fill.

### USES

- ◆ For filling large or small holes, nailheads, nail hole, cracks in concrete, masonry, plaster and wood.

**WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS**

### NOT RECOMMENDED FOR

Snowfiller light weight sparkling compound is less-flexible filling compound and only recommended for internal use only.  
Not for: use in areas of water immersion.  
Not for: nailing or strong supporting.  
Not for: use on plastic or metal surfaces.  
Not for: movement joint

### COLOUR

White colour when it is dry

### APPLICATION

- ◆ Surface must be clean, dust and grease free.
- ◆ Apply filler with a putty knife into the crack or gap which requires filling. If the filler feels too dry, mix with a few drops of water.
- ◆ Fill all sizes of holes and cracks in one application.
- ◆ Smooth finish in one stroke using a putty knife.
- ◆ Sandable and paintable when the patched surface is white in colour.
- ◆ Clean tools with water immediately after use.

### CURING TIME

Snowfiller light weight sparkling compound will set within 1 - 2 hours. Longer drying times may be necessary for large holes or in cold and high humidity area.

# x'traseal®



# SNOW FILLER

LIGHT WEIGHT SPARKLING COMPOUND

## TECHNICAL DATA SHEET

REV: 04

Date: 30 April 2024

### SPECIFICATION

Base	Acrylic latex
Appearance	Non-sagging paste
Colour	White
Specific gravity	0.45 ± 0.1
Solid contents	70% approx.
Tack free time	1 – 2 hours
Application temp.	5°C to 50°C
Service temp.	-10°C to 80°C
Shelf life	12 months

### STORAGE

Material should be stored in a dry and cool place between +5°C to +30°C.

### CAUTION

Read and understand material safety data sheet of this product before handling or using.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)  
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,  
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919  
Website: www.xtraseal.com Email: info@mochem.com