



1101

LIQUID GASKET

x'traseal®

TECHNICAL DATA SHEET

REV: 05

Date: 25 April 2024

DESCRIPTION

x'traseal® 1101 LIQUID GASKET is a semi-drying gray liquid gasket that uses rubber as the main ingredients. It is formulated to form a layer thick enough to work efficiently on uneven joint surfaces. It has a distinguishing ability to turn into rubber-like elastic substances with excellent resistance to heat, oil, gasoline and particularly LPG. Ideal for the purpose of making quality gaskets in garages, workshops, homes and do-it-yourself.

FEATURES

- A visco-elastic type sealant capable of joining uneven surfaces.
- Excellent resistance to heat, oil, gasoline and lpg.
- Easy to apply and allow to automate the production line with labor-saving equipments, markedly improving the work efficiently.
- Has the property of flowing at room temperature.

USES

For the purpose of making quality gaskets in garages, workshops, homes and do-it-yourself.

Due to a large variety of different coatings and substrates, we recommend preliminary compatibility tests prior to application to achieve desirable results

APPLICATION

- Surfaces must be clean, dry, and free from moisture, grease and other stains before application.
- Apply a thin and uniform layer of liquid gasket on both mating surfaces.
- Assemble about 1 minute after application.
- Application temperature range is from -40°C to +150°C.
- Seal tightly after use. Store in a cool dry place.

SPECIFICATION

Appearance	Gray High Viscosity Liquid
Specific Gravity	1.05 ± 0.05
Solid Content	>48%
Main Solvent	Hydrocarbon Solvent
Main Ingredient	Chloroprene Rubber
Dilution	Toluene
Temperature Range	40°C To 150°C
Shelf life	12 months

STORAGE

Material Should Be Stored In A Dry And Cool Place Between +50C TO +300C.



1101

LIQUID GASKET

x'traseal®

TECHNICAL DATA SHEET

REV: 05

Date: 25 April 2024

CAUTION

Read And Understand Material Safety Data Sheet Of This Product Before Handling Or Using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com

Mohm Chemical Sdn. Bhd. is an ISO14001 & ISO9001 certified company in Malaysia. x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd. ©1993 Mohm Chemical Sdn. Bhd. All rights reserved.