

BT-390

WINDSCREEN SEALANT (BUTYL TAPE)

DESCRIPTION:

x'traseal® BT-390 Windscreen Sealant (Butyl Tape) is a black, non-hardening synthetic rubber based. It is a sticky ribbon type auto glass replacement sealer used for the installation of all gaskets less windshields and backlites. BT-390 offers a fast and clean method for installing the glass. Instantly with superior adhesion. The sealer has excellent compressibility in both low / high temperatures. It is designed to maintain position, permanently sealing and waterproofing between the glass and pinch weld.

SPECIFICATION:

Base	Butyl rubber
Appearance	Black
Hardness IRHD	25 ± 1
Specific gravity	1.4 ± 0.10
Heat resistance	100°C
Water resistance	Excellent
Service temperature	- 20°C to 70°C
Ordor	Non or very little
Adhesion	Good on metal, glass, wood and concrete
Storage	Product is very inert and can last almost indefinitely without deteriorating (Best before 12 months from production)

APPLICATION:

- ◆ Remove the windshields and old sealant material from surfaces thoroughly.
- ◆ Surface must be clean, dry and free from grease, oil and dirt.
- ◆ Hand pressed the tape into place ground the pinch weld. Replace new setting blocks if original blocks are damaged.
- ◆ Place the windscreen over the tape and apply pressure evenly to ensure water tight achieved.

TIPS:

- ◆ This tape can be used alone or in combination with other sealants, eg. Polyurethane or silicone sealant depending upon the type of installation.

- ◆ In extremely cold weather conditions, it is recommended to warm the butyl tape for the better workability.

CAUTION:

Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

