



PUTTY FILLER

TECHNICAL DATA SHEET

REV: 05

Date: 30 April 2024

DESCRIPTION

Putty Filler is a ready to use filler for interior. It is an acrylic based formulation used for both bedding and finishing together with joint tape to reinforce and conceal the joints, fasteners and corner bead of gypsum board. It can also be used to texture wallboard surfaces and laminate wallboard to an existing surface such as old plaster, masonry or gypsum wallboard. Due to its ready mixed formulation it is time saving with minimal wastage and is thus highly economical and convenient to use.

USES

Cement plaster, concrete and brick, emulsion and cement paint asbestos, cemboard and gypsum board joint.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

SPECIFICATION

Adhesion	Adheres firmly to all clean, dry and grease free plaster and wood surfaces. Will not crack or fall out when dry.
Colour	White
Specific gravity	1.73 ± 0.2
Drying time	A thin film dries in approx. 15 to 30 minutes.
Sandability	Use 150 grit sandpaper
Odour	Odourless after dry
Coverage	30 to 40 square feet per kg
Safety	Non-flammable and non-toxic
Cleaning	Clean tools with water
Shelf Life	12 months

STORAGE

Material should be stored in a dry and cool place between +5^oc to +30^oc.

CAUTION

Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.