



x'traseal®

SAFETY DATA SHEET

WP-715

XTRASLATE 208

REV: 01

Date: 11 JUN 2024

1. Product & Company Identification

Product Details

Product name: WP-715 XTRASLATE 208
Physical form: Transparent Protecting Acrylic Coating
Odour: Mild odour
CAS No.: Mixture
Flammability: Non-flammable

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal word: Danger

GHS Classification:

Flammable Liquids	Category 3
Acute Toxicity - Dermal	Category 4
Acute Toxicity - Inhalation	Category 4
Aspiration Hazard	Category 1
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Irritation	Category 2A
Specific Target Organ Toxicity (Single Exposure) Respiratory Tract Irritation	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 1

Hazard statement

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.



MOHM CHEMICAL SDN. BHD. (REGNO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



x'traseal®

SAFETY DATA SHEET

WP-715

XTRASLATE 208

REV: 01

Date: 11 JUN 2024

H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H401 Toxic to aquatic life.

Precautionary Statement - Prevention

P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe fumes, mist, vapours or spray.
P261 Avoid breathing fumes, mist, vapours or spray.
P264 Wash hands, face and all exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator

Precautionary Statement - Response

P101 If medical advice is needed, have product container or label at hand.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse

Precautionary Statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up

Precautionary Statement – Disposal

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.



x'traseal®

WP-715

XTRASLATE 208

SAFETY DATA SHEET

REV: 01

Date: 11 JUN 2024

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Acrylate Resin	108-88-3	50 – 60 %
Xylene	1330-20-7	40 – 45%

4. First-aid Measures

Take off all contaminated clothing immediately.	
In case of inhalation:	Get medical aid immediately. Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
In case of ingestion:	Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. Seek medical advice immediately.
In case of skin contact:	Wash the affected with plenty of running water and mild soap. If irritation continues, immediately consult a physician for examination and treatment.
In case of eyes contact:	Immediately flush eyes with water with plenty of water for at least 15 minutes. Get medical aid if irritation develops or persists.

5. Fire Fighting Measures

Flammable limits	Not applicable
Suitable extinguishing media:	use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).
Specific hazards:	Flammable liquid and vapour.

6. Accidental release measures

Step to be taken if materials is spilled or released:	Provide adequate ventilation and clean up with water before allowing drying. Do not discharge into drains or rivers. Observe government regulations.
Waste disposal method:	Contain spills with earth, sand, or similar stable, non-combustible material. Incinerate contaminated materials at an authorized installation.

7. Handling and Storage

Handling:	Keep material away from sparks, flames, and other ignition sources.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Store at cool dry place.

8. Exposure control / Personal protection

Local exhaust:	Exhaust directly to the outside , Treatment of exhaust emission to prevent. Environmental controlling may be required.
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/ protective glasses.
Respiratory Protection:	Respirator
Skin and Body Protection:	Wear appropriate protective gloves and clothing to prevent and minimize contact with skin.



MOHM CHEMICAL SDN. BHD. (REGNO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



x'traseal®

SAFETY DATA SHEET

WP-715

XTRASLATE 208

REV: 01

Date: 11 JUN 2024

9. Physical and Chemical Properties

Form:	liquid
Specific gravity:	0.9
Colour:	Transparent
Viscosity:	-
Odour:	Aromatic odour
Decomposition temperature:	350°C
Flash Point :	50°C
Vapour Pressure:	Not applicable
Vapour Density:	<1.0
Solubility:	None
pH:	Not applicable

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:	Stable at room temperature.
Incompatibility (material to be avoid):	Strong oxidizer, caustics, acid
Hazardous decomposition products:	Combustion may produce carbon dioxide, carbon monoxide.
Hazardous polymerization:	Will not occur.

11. Toxicological Information

Ingestion: Moderately toxic. This product may irritate the throat and stomach.
Eye contact: Severe irritant. This product may cause an inflammation of the eye.
Skin contact: Mild irritant. This product may cause an irritation or a rash to develop.
Inhaled: Toxic. Inhalation of the product's vapour may cause headaches, drowsiness and loss of consciousness.

12. Ecological Information

Avoid contaminating waterways
Information relevant to the impact if the material if released to the environment :

a) Acute & long-term toxicity tests on birds, fish, plants & etc.:	Not available
b) Transportation, transports & fate:	Not available
c) Potential for accumulation:	Not available



x'traseal®

SAFETY DATA SHEET

WP-715

XTRASLATE 208

REV: 01

Date: 11 JUN 2024

13. Disposal considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations. Dispose to an authorised waste collection point. Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.

14. Transport Information

ROAD AND RAIL TRANSPORT

Proper shipping name: RESIN SOLUTION.
UN or NA number : 1866
Classification or hazard class: 3
Packing group III

MARINE TRANSPORT(IMDG)

Proper shipping name: RESIN SOLUTION.
UN or NA number : 1866
Classification or hazard class: 3
Packing group III

AIR TRANSPORT(IATA)

Proper shipping name: RESIN SOLUTION.
UN or NA number : 1866
Classification or hazard class: 3
Packing group III

This product is not classified as dangerous goods according to the international regulation for transport by land, inland waterway, sea and air.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements of EC directives.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***