



SUPER GLUE

TECHNICAL DATA SHEET

REV: 04

Date: 30 April 2024

DESCRIPTION

Super Glue is a cyanoacrylate adhesive that set within seconds to form a strong bond on most of the smooth surface. It works well on both porous and non-porous materials. The adhesive can be use to bond most of the metal, wood, rubbers, plastics, leather, ceramics, glass and fabric.

FEATURES:

- ◆ Easy to apply.
- ◆ Fast setting within seconds.
- ◆ Strong bonding strength, especially on smooth surface without gap.
- ◆ Cost saving.

USE

Bonding most of the metals, wood, rubbers, plastics, leather, ceramics, glass and fabric.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR

Not use for: areas of constant water immersion.
Not for: PE, PP, PTFE and bituminous surface.

APPLICATION

- ◆ Surface must be clean, dry and free from grease and old glue.
- ◆ Mask smooth surface to simplify clean up.
- ◆ Apply to one surface only.
- ◆ Apply suitable pressure on bonding substrates.
- ◆ Clean off excess adhesive with acetone.

CURING TIME

Contact adhesive will bond in approximately 30 - 45 seconds under room temperature.

SPECIFICATION

Appearance	Clear Liquid.
Odour	Pungent Smell.
Specific Gravity	1.05 ± 0.05
Viscosity	100 CPS Approx.
Application Temp.	-10°C To 40°C
Service Temperature	-10°C To 60°C
Shelf Life	12 Months @ 20°C

x'traseal®



SUPER GLUE

TECHNICAL DATA SHEET

REV: 04

Date: 30 April 2024

STORAGE

Material should be stored in a dry and cool place below +20°C.

CAUTION

Super glue bonds skin and eyes in seconds. Read and understand material safety data sheet of this product before handling or using.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.